


## GET IN TOUCH

-  (563) 875-6257
-  sales@doublel.com
-  2020 Beltline Rd, Dyersville, IA 52040.



”  
**WHERE  
AFFORDABILITY  
MEETS TECHNOLOGY  
SINCE 1973**

”

## **DIRECTX** EXHAUST FANS

Helping Growers with EC3 Technology

Since 1973, Double L Group has been committed to providing high-quality products and services worldwide that are based on value, customer's needs, and excellent sales support.

# TECHNICAL DATA

Model	Part Number	Imp. Dia.	Fan Speed	RPM	Motor HP	.05" SP		.1" SP		.15" SP	
						CFM	CFM/Watt	CFM	CFM/Watt	CFM	CFM/Watt
DIRECTX36	DIRECTX362WS	36	100%	950	1.25	15,070	22.0	14,350	19.9	13,460	17.8
			90%	850		13,390	26.3	12,450	22.6	11,490	20.0
			80%	750		11,400	30.8	10,130	25.8	8,850	21.7
			70%	650		9,340	35.4	7,930	28.2	6,030	21.4
DIRECTX51	DIRECTX512WS	51	100%	690	2.5	32,063	20.0	30,632	18.0	29,152	17.0
			90%	621		28,634	24.0	27,124	22.0	25,263	19.0
			80%	552		25,176	30.0	22,941	25.0	21,624	23.0
			70%	483		21,465	36.0	19,509	30.0	16,649	24.0
DIRECTX57	DIRECTX572WS	57	100%	690	3	36,700	22.7	35,000	19.6	33,000	17.6
			90%	620		32,200	26.4	30,400	22.9	28,600	20.0
			80%	550		28,600	31.9	26,200	26.6	23,800	22.7
			70%	450		22,200	42.2	18,600	32.1	13,700	23.0

## FEATURES

- Fiberglass Reinforced SMC Shell
- Brushless Magnet Motor
- Incorporated Dampers
- Robust Direct-Drive Structure

## BENEFITS

- Ensures large air volume, high efficiency, and excellent corrosion resistance.
- Offers high efficiency, a wide operating range, strong load capacity, and stable high-speed performance. Includes intelligent digital control for convenient operation.
- Improves operational reliability while maintaining high air volume. Features a special alloy door panel for strength, deformation resistance, and superior sealing.
- Lowers failure rates and ensures substantial air volume output even under high negative pressure conditions.

”

WE STRIVE TO PROVIDE OUR DISTRIBUTORS AND CUSTOMERS WITH INNOVATIVE PRODUCTS WITH A GREAT RETURN ON INVESTMENT.

